



XonTel

S10P IP-Door intercom
For your Home & Office

Smart Security

XONTEL security intercom series IP Intercom S10P is well developed according to customers requirements based on VOIP Phone. It has Fashion classic aluminum wire drawing surface shell with the design of waterproof, dustproof, anti-dismantle. The traits of strong compatibility and supporting extra access swiping card device make it perfectly to be used in bank, subway, power plant, mine, prison, steel companies and so on. It is the best choice and highly cost effective for customers' projects requirements in this industry.

Key Features

- One key to dial emergency call for help, realize the bi-directional full-duplex voice intercom.
- Panel adopts advanced wire drawing aluminum alloy material, high strength damage resistant button, strong and durable.
- Support POE power supply and the external power supply.
- Embedded wall or mounted in the wall, to avoid cable leakage users, to ensure that the internal network information security, provide and remote configuration.
- Built-in speaker and high sensitive microphone, support hand-free calls and receive emergency broadcast
- Adopted seal design, waterproof and dustproof level is IP65.
- Support extra access security device, multi-functions provide more perfect service to industry customers.

S10P Technical Datasheet

Phone Features

WEB support Multi-Language
1 SIP account, Hotline
Call hold, Call waiting, Call forward
Call transfer (blind/busy/ask)
Mute, DND
Auto-answer, 3-way conferencing
1 DSS programmable key(Speed dial, Intercom etc.)
Volume control
Direct IP call without SIP proxy
Default Ring tone 1 selection/import/delete
Custom Warning Ring tone 2 selection/import/delete
Time setting(SNTP/SIP Server/Manual)
Support SIP main/standby server

Advanced Features

1 key to restore the factory value
1 DSS programmable key(Speed dial, Intercom etc.)
2 input and 2 output control interface, can connect other security equipment
1 recording interface, 1 custom warning ring tone interface(using Ring tone 2)

IP PBX System Integration

Busy lamp field (BLF), BLF list
Bridged line appearance (BLA)
DND & Forward synchronization
Intercom, Paging, Music on hold
Call pickup, Dial Plan, Call recording Anonymous call, Anonymous call rejection

Compatible with the platform



Codes and Voice Features

Wideband Codec: G.722
Narrowband codec: G.711µ/A, G.723.1
G.726, G.729a/b, iLBC
VAD, CNG, AEC, AGC
Full-duplex,

Security

LLDP, VLAN QoS (802.1pq), VPN(L2TP)
Transport Layer Security (TLS)
Digest authentication using MD5/MD5-sess
Secure configuration file via AES encryption
Phone lock for personal privacy protection
Admin/User 2-level configuration mode

Network Features

SIP v1 (RFC2543), v2 (RFC3261)
DNS SRV (RFC3263)
NAT Traversal: STUN mode
DTMF: In-Band, RFC2833, SIP Info, Auto
HTTP/HTTPS Web Management
IP Assignment: Static/DHCP/PPPoE
Network support Bridge mode
TFTP/DHCP/PPPoE client
DNS client, NAT/DHCP server

Management

Auto-provision via FTP/TFTP/HTTP/HTTPS
SNMP V1/2, TR069 optional
Configuration: browser/phone/auto-provision
Trace package and system log export

Physical Features

1 DSS programmable key(Speed dial, Intercom etc.)
1 LED lights.
1 light touch button(Remote factory value)
1xRJ45 10/100M Ethernet ports
Power adapter: AC 100~240V input and DC 12V/1A output
Power over Ethernet ,IEEE 802.3af,class 0
Net weight: 0.52KG, Gross weight: 0.65KG
Dimension: 162x112x40MM
Operating humidity: 10~95%
Storage temperature: up to 60°C

Package Features

Qty/CTN: 20 PCS
N.W/CTN: 10.4KG
G.W/CTN: 13KG
Carton Meas: 365*365*270MM

Certifications



XonTel | www.sahabtec.com

Follow us on



Kuwait

Tel : +965 - 188 0005
Fax : +965 - 2241 38 77

Saudi Arabia

Toll Free : 92000 76 22
Fax : +966 - 011- 4700403

Bahrain

Toll Free : 8000 10 15
Fax : +973 - 178 22 512